

ANNUAL HOUSE WOF

P	F	Exterior					
		Exterior Cladding					
		Roof	Roof Cladding				
		Watertightness					
		Joinery					
		Structually sound					
		Glass doors made of safety glass or include visibility strips					
		Handrails and balustrades					
		Deck					
		Paths and surfaces non-slippery/free from moss					
		• • • • • • • • • • • • • • • • • • • •					
		Spouting, storm/waste water functioning, no leaks					
	_	Artificial lighting - other					
PF		Entrance Address de la labella de calcida di Cicilia					
		Address clearly labelled and identifiable					
		Securely locking doors					
		Working light					
PF		Ceiling Insulation					
		Insulation to requirements (120mm)					
		No gaps, tucks or folds					
		No dampness in insulation					
		Clearance for lights, ducts and roof					
PF		Underfloor Insulation					
		Insulation to requirements					
		Dry underfloor					
		Ground vapour barrier					
		No ponding					
1 2		3 4 5 Bedrooms					
PF	PF	PF	PF	PF			
					Wall, ceiling and floor linings intact		
					Surfaces clear of mould		
					Effective ventilation to the outside		
					Opening window with secure latch		
					Window security stays (if required)		
					Visibly safe power & light switches		
					Smoke alarm within 3m		
	_	11-11	- 10		Curtains/blinds/double glazing		
PF		Hallway/Stairwell					
		Wall, ceiling and floor linings intact					
		Surfaces clear of mould					
		Visibly safe power outlets & light switches					
		Opening window with secure latch					
		Window security stays (if required)					
		Artificial lighting					
		Stairs & handrails					
P	F	Services					
		Plumbing					
		Electrical					
		Heating					

Assessment Checkist

P=Pass F=Fail /=Not applicable

PF	Kitchen					
	Wall, ceiling and floor linings intact					
	Surfaces clear of mould					
	Functioning stove and oven					
	Effective ventilation to the outside					
	Opening window with secure latch					
	Window security stays (where required)					
	Adequate food preparation and storage					
	Hot water at tap (55 degress +/- 5 degrees)					
	Potable water supply					
	Waste water drainage with sound connection					
	Visibly safe power outlets & light switches					
	Working artificial lighting					
PF	Living Area					
	Wall, ceiling and floor linings intact					
	Surfaces clear of mould					
	Effective ventilation to the outside					
	Opening window with secure latch					
	Window security stays (where required)					
	Working artificial lighting					
	Heating, fixed, effective & safe					
	Visibly safe power outlets & light switches					
	ICurtains/blinds/double glazing present					
PF	Curtains/blinds/double glazing present Bathroom and Toilet					
PF	Bathroom and Toilet					
PF	Bathroom and Toilet Wall, ceiling and floor linings intact					
PF	Bathroom and Toilet Wall, ceiling and floor linings intact Surfaces clear of mould					
PF	Bathroom and Toilet Wall, ceiling and floor linings intact Surfaces clear of mould Operational Toilet					
PF	Bathroom and Toilet Wall, ceiling and floor linings intact Surfaces clear of mould Operational Toilet Sewage connection functional					
PF	Bathroom and Toilet Wall, ceiling and floor linings intact Surfaces clear of mould Operational Toilet Sewage connection functional Functioning bath or shower					
PF	Bathroom and Toilet Wall, ceiling and floor linings intact Surfaces clear of mould Operational Toilet Sewage connection functional Functioning bath or shower Effective ventilation to the outside					
PF	Bathroom and Toilet Wall, ceiling and floor linings intact Surfaces clear of mould Operational Toilet Sewage connection functional Functioning bath or shower Effective ventilation to the outside Opening window with secure latch					
PF	Bathroom and Toilet Wall, ceiling and floor linings intact Surfaces clear of mould Operational Toilet Sewage connection functional Functioning bath or shower Effective ventilation to the outside Opening window with secure latch Window security stays (where required)					
PF	Bathroom and Toilet Wall, ceiling and floor linings intact Surfaces clear of mould Operational Toilet Sewage connection functional Functioning bath or shower Effective ventilation to the outside Opening window with secure latch Window security stays (where required) Waste water drain connected					
PF	Wall, ceiling and floor linings intact Surfaces clear of mould Operational Toilet Sewage connection functional Functioning bath or shower Effective ventilation to the outside Opening window with secure latch Window security stays (where required) Waste water drain connected Hot water at tap (55 degress +/- 5 degrees)					
PF	Bathroom and Toilet Wall, ceiling and floor linings intact Surfaces clear of mould Operational Toilet Sewage connection functional Functioning bath or shower Effective ventilation to the outside Opening window with secure latch Window security stays (where required) Waste water drain connected Hot water at tap (55 degress +/- 5 degrees) Visibly safe power outlets & light switches					
	Wall, ceiling and floor linings intact Surfaces clear of mould Operational Toilet Sewage connection functional Functioning bath or shower Effective ventilation to the outside Opening window with secure latch Window security stays (where required) Waste water drain connected Hot water at tap (55 degress +/- 5 degrees) Visibly safe power outlets & light switches Working artificial lighting					
PF	Bathroom and Toilet Wall, ceiling and floor linings intact Surfaces clear of mould Operational Toilet Sewage connection functional Functioning bath or shower Effective ventilation to the outside Opening window with secure latch Window security stays (where required) Waste water drain connected Hot water at tap (55 degress +/- 5 degrees) Visibly safe power outlets & light switches Working artificial lighting Laundry					
	Wall, ceiling and floor linings intact Surfaces clear of mould Operational Toilet Sewage connection functional Functioning bath or shower Effective ventilation to the outside Opening window with secure latch Window security stays (where required) Waste water drain connected Hot water at tap (55 degress +/- 5 degrees) Visibly safe power outlets & light switches Working artificial lighting Laundry Wall, ceiling and floor linings intact					
	Wall, ceiling and floor linings intact Surfaces clear of mould Operational Toilet Sewage connection functional Functioning bath or shower Effective ventilation to the outside Opening window with secure latch Window security stays (where required) Waste water drain connected Hot water at tap (55 degress +/- 5 degrees) Visibly safe power outlets & light switches Working artificial lighting Laundry Wall, ceiling and floor linings intact Surfaces clear of mould					
	Wall, ceiling and floor linings intact Surfaces clear of mould Operational Toilet Sewage connection functional Functioning bath or shower Effective ventilation to the outside Opening window with secure latch Window security stays (where required) Waste water drain connected Hot water at tap (55 degress +/- 5 degrees) Visibly safe power outlets & light switches Working artificial lighting Laundry Wall, ceiling and floor linings intact Surfaces clear of mould Effective ventilation to the outside					
	Wall, ceiling and floor linings intact Surfaces clear of mould Operational Toilet Sewage connection functional Functioning bath or shower Effective ventilation to the outside Opening window with secure latch Window security stays (where required) Waste water drain connected Hot water at tap (55 degress +/- 5 degrees) Visibly safe power outlets & light switches Working artificial lighting Laundry Wall, ceiling and floor linings intact Surfaces clear of mould Effective ventilation to the outside Working artificial lighting					
	Wall, ceiling and floor linings intact Surfaces clear of mould Operational Toilet Sewage connection functional Functioning bath or shower Effective ventilation to the outside Opening window with secure latch Window security stays (where required) Waste water drain connected Hot water at tap (55 degress +/- 5 degrees) Visibly safe power outlets & light switches Working artificial lighting Laundry Wall, ceiling and floor linings intact Surfaces clear of mould Effective ventilation to the outside Working artificial lighting Waste water drain connected					
PF	Wall, ceiling and floor linings intact Surfaces clear of mould Operational Toilet Sewage connection functional Functioning bath or shower Effective ventilation to the outside Opening window with secure latch Window security stays (where required) Waste water drain connected Hot water at tap (55 degress +/- 5 degrees) Visibly safe power outlets & light switches Working artificial lighting Laundry Wall, ceiling and floor linings intact Surfaces clear of mould Effective ventilation to the outside Working artificial lighting Waste water drain connected Visibly safe power outlets and light switches					
	Wall, ceiling and floor linings intact Surfaces clear of mould Operational Toilet Sewage connection functional Functioning bath or shower Effective ventilation to the outside Opening window with secure latch Window security stays (where required) Waste water drain connected Hot water at tap (55 degress +/- 5 degrees) Visibly safe power outlets & light switches Working artificial lighting Laundry Wall, ceiling and floor linings intact Surfaces clear of mould Effective ventilation to the outside Working artificial lighting Waste water drain connected Visibly safe power outlets and light switches Other					
PF	Wall, ceiling and floor linings intact Surfaces clear of mould Operational Toilet Sewage connection functional Functioning bath or shower Effective ventilation to the outside Opening window with secure latch Window security stays (where required) Waste water drain connected Hot water at tap (55 degress +/- 5 degrees) Visibly safe power outlets & light switches Working artificial lighting Laundry Wall, ceiling and floor linings intact Surfaces clear of mould Effective ventilation to the outside Working artificial lighting Waste water drain connected Visibly safe power outlets and light switches					

Totals Pass	Fail
-------------	------